
CLAIMS

1. (Currently amended) An automatic phase and frequency adjust circuit, comprising:

a phase locked loop circuit adapted to generate a phase locked loop clock responsive to a reference signal;

an edge detector circuit adapted to generate an edge pulse signal corresponding to a transition of an analog data signal responsive to a pixel clock;

a phase detector circuit adapted to ~~identify a phase of the phase locked loop clock associated to the transition of the analog data and thereby~~ generate a phase adjust signal responsive to a phase of the phase locked loop clock and the edge pulse signal; and

a phase adjust circuit adapted to generate a the pixel clock by adjusting the phase of the phase locked loop clock responsive to the phase adjust signal and the phase locked loop clock.

2. (Original) The automatic phase and frequency adjust circuit of claim 1 wherein the phase locked loop circuit comprises:

a phase detector adapted to receive the reference signal;

a loop filter coupled to the phase detector;

a voltage controlled oscillator coupled to the loop filter;

a feedback loop adapted to receive the phase locked loop clock and provide a feedback signal responsive to a frequency adjust signal.

3. (Original) The automatic phase and frequency adjust circuit of claim 1 wherein the reference signal is a horizontal synchronization signal.

4. (Currently amended) The automatic phase and frequency adjust circuit of claim 1 wherein the edge detector ~~is adapted to~~ generates an edge pulse corresponding to the transition of the analog data signal above a predetermined threshold.

5. (Original) The automatic phase and frequency adjust circuit of claim 4 wherein the threshold is programmable.

6. (Currently amended) The automatic phase and frequency adjust circuit of claim 1 wherein the edge detector ~~is adapted to~~ generates an edge pulse corresponding to a rising, falling, or both rising and falling edges of the analog data signal.

7. (Currently amended) The automatic phase and frequency adjust circuit of claim 1 wherein the phase adjust circuit ~~is adapted to~~ adjusts the phase of the pixel clock by delaying the reference signal.

8. (Currently amended) The automatic phase and frequency adjust circuit of claim 1 wherein the phase adjust circuit ~~is adapted to~~ adjusts the phase of the pixel clock by delaying the phase locked loop clock.

a'
9. (Currently amended) The automatic phase and frequency adjust circuit of claim 8 wherein the phase adjust circuit comprises:

a clock delay circuit adapted to generate a plurality of delayed clock signals by delaying the phase locked loop clock; and

a multiplexer adapted to select one of the plurality of delayed clock signals as the pixel clock responsive to a phase adjust signal.

10. (Original) The automatic phase and frequency adjust circuit of claim 9 wherein the clock delay circuit comprises an n-stage delay locked loop, each stage generating a corresponding delayed clock phase, each delayed clock phase being $360/n$ degrees out of phase.

11. (Currently amended) The automatic phase and frequency adjust circuit of claim 1

wherein the phase adjust circuit generates a plurality of delayed clock signals by delaying the phase locked loop clock; and

wherein the phase detector comprises:

a phase hit detector adapted to generate a plurality of phase hit enable signals corresponding to the plurality of delayed clock signals and assert one of the phase hit enable signals responsive to the edge pulse signal; and

a phase hit counter adapted to count asserted phase hit enable signals for each of the delayed clock signals over a predetermined time.

12. (Original) The automatic phase and frequency adjust circuit of claim 11 wherein the predetermined time is a number of image scan lines.

13. (Currently amended) The automatic phase and frequency adjust circuit of claim 11 wherein the phase hit detector comprises:
a plurality of flip-flop circuits corresponding to the plurality of delayed clock signals adapted to generate a corresponding plurality of phase out signals; and
a comparison circuit adapted to comparing the plurality of phase out signals.

14. (Currently amended) The automatic phase and frequency adjust circuit of claim 13 wherein the comparison circuit is adapted to compare adjacent phase out signals.

15. (Currently amended) The automatic phase and frequency adjust circuit of claim 11 wherein the phase hit counter comprises:
an enable signal adapted to enable counting of asserted phase hit enable signals; and
a clear signal adapted to clear the phase hit counter.

16. (Currently amended) The automatic phase and frequency adjust circuit of claim 11 comprising:
a phase count analysis circuit adapted to generate phase and frequency adjust signals by analyzing the count of asserted phase hit enable signals.

17. (Currently amended) The automatic phase and frequency adjust circuit of claim 1 comprising an auto calibration circuit adapted to align the analog data signal with the pixel clock.

18. (Currently amended) A circuit, comprising:
an edge detector adapted to generate an edge pulse corresponding to a transition of an analog image signal responsive to a pixel clock;
a phase adjust circuit adapted to generate a the pixel clock signal by adjusting a phase of a phase locked loop clock signal derived from a reference signal responsive to a phase adjust signal; and

a phase detector circuit adapted to generate the phase adjust signal responsive to the edge pulse signal.

19. (Currently amended) The circuit of claim 18 wherein the edge detector is adapted to generate the edge pulse signal responsive to a transition of the analog signal greater than a predetermined threshold.

20. (Currently amended) The circuit of claim 18 wherein the edge detector is adapted to generate the edge pulse responsive to a rising, falling, or both rising and falling edges of the analog image signal.

21. (Original) The circuit of claim 18 wherein the edge detector comprises a calibration circuit adapted to calibrate the analog image signal with the pixel clock.

22. (Currently amended) The circuit of claim 18 wherein the phase adjust circuit is adapted to generate the pixel clock by delaying the a reference signal.

23. (Currently amended) The circuit of claim 18 wherein the phase adjust circuit comprises:

a delay locked loop adapted to generate a plurality of clock phases by delaying the phase locked loop clock signal derived from the reference signal; and

a multiplexer adapted to select one of the plurality of delayed clock signals as the pixel clock responsive to the phase adjust signal.

24. (Original) The circuit of claim 23 wherein the delay locked loop includes n stages, each clock phase being $360/n$ degrees out of phase.

25. (Original) The circuit of claim 18

wherein the phase adjust circuit comprises a clock delay circuit adapted to generate a plurality of clock phases by delaying the phase locked loop clock signal derived from the reference signal;

wherein the phase detector circuit comprises:

a phase hit enable signal corresponding to each of the plurality of clock phases, the phase hit enable signal being asserted responsive to the edge pulse signal;

a count corresponding to each of the plurality of clock phases, the count being indicative of a number of assertions of a corresponding phase hit enable signal over a predetermined time.

26. (Currently amended) The circuit of claim 25 wherein the phase detector circuit comprises:

an enable signal ~~adapted~~ to enable the phase detector circuit; and
a clear signal ~~adapted~~ to clear each count.

27. (Original) The circuit of claim 25 wherein the predetermined time is a number of image scan lines.

28. (Currently amended) The circuit of claim 25 wherein the phase detector circuit is ~~adapted to~~ generate the phase adjust signal by analyzing the count.

29. (Currently amended) The circuit of claim 25 comprising a phase locked loop circuit ~~adapted to~~ derive the phase locked loop clock signal from the a reference signal responsive to a frequency adjust signal.

30. (Currently amended) The circuit of claim 29 wherein the phase detector circuit is ~~adapted to~~ generates the phase and frequency adjust signals by analyzing each count.

31. (Currently amended) A method for automatically adjusting a phase and frequency of a pixel clock in a digital image system, comprising:
generating a plurality of clock phases by delaying a phase locked loop clock signal by a plurality of delays;
detecting a transition of an analog image signal responsive to a pixel clock signal;
asserting a clock phase hit by determining which of the clock phases corresponds to the transition;
counting a number of clock phase hits for each of the clock phases; and
a-generating a phase and frequency adjust signal as a result of the counting.

32. (Currently amended) The method of claim 31 comprising deriving the phase locked loop clock signal from a reference signal responsive to the frequency adjust signal.

33. (Original) The method of claim 31 comprising selecting a clock phase as the pixel clock responsive to the phase adjust signal.

34. (Original) The method of claim 31 wherein detecting a transition includes detecting a transition of the analog image signal above a predetermined threshold.

35. (Original) The method of claim 31 wherein detecting a transition includes detecting a rising, falling, or both rising and falling edges of the analog image signal.

a' 36. (Currently amended) The method of claim 31 wherein detecting a transition includes generating an edge pulse responsive to the transition and wherein asserting a clock phase hit includes comparing the edge pulse with each of the clock phases.

37. (Original) The method of claim 31 wherein asserting the clock phase hit includes generating a plurality of clock phase hit signals corresponding to the plurality of clock phases and asserting only the clock phase hit signal closest to the transition.

38. (Original) The method of claim 31 wherein counting the number includes counting the number of clock phase hits for each of the clock phases over a predetermined time.

39. (Original) The method of claim 38 wherein the predetermined time is a number of image scan lines.

40. (Original) The method of claim 31 wherein counting includes:
clearing the counting; and
enabling the counting.

41. (Original) The method of claim 31 wherein counting includes generating a count for each of the clock phases and wherein counting comprises:
examining the count; and

adjusting the frequency of the pixel clock if the count exceeds a predetermined number.

Q, 42. (Currently amended) The method of claim 41 wherein adjusting the frequency of the pixel clock comprises:

changing the frequency of the phase locked loop clock signal;

clearing the count;

enabling the count;

repeating the counting, examining, and adjusting if the count exceeds a predetermined number.
